














钻孔柱状图

工程名称					东莞市桥头镇东太湖产业园规划一路道路工程					工程编号		GDZS2525-026	
孔 号		LK1		坐 标	X=2547280.331m		钻孔直径		稳定水位深度		1.90m		
孔口标高		7.70m			Y=38512789.064m		初见水位深度		测量日期		2025.6.13		
地质时代	层号	层底 标高 (m)	层底 深度 (m)	分层 厚度 (m)	柱状图 1:150	地 层 描 述				取 样 编 号 深度(m)	标贯 实测 击数(击) 深度(m)		
q ₄ ^{al}	①	4.40	3.30	3.30		素填土:灰褐色、红褐色,松散,主要由粘性土填成,夹碎石、砼块,顶部约0.2米为砼路面。				1 2.30-2.50	13.0 2.65-2.95		
	② ₁	0.90	6.80	3.50		粉质黏土:黄褐色、灰褐色,软塑-软可塑,切面较光滑,粘性及韧性较好,干强度较高。				2 4.70-4.90	5.0 5.15-5.45		
	② ₂	-6.80	14.50	7.70		淤泥质土:灰黑色、深灰色,流塑,具腥臭味,夹砂、局部夹腐木。				3 9.30-9.50	3.0 9.75-10.05		
	② ₃	-10.10	17.80	3.30		中细砂:灰褐色,松散-稍密,饱和,主要成分为石英,级配差,砂质不存,局部夹淤泥。				4 15.60-15.80	14.0 16.05-16.35		
广东中盛市政工程设计有限公司 外业日期: 2025.6.12													
制表:									校核: 				



钻 孔 柱 状 图

工程名称		东莞市桥头镇东太湖产业园规划一路道路工程					工程编号		GDZS2525-026				
孔 号		LK2		坐		X=2547337.646m		钻孔直径		稳定水位深度		2.90m	
孔口标高		8.90m		标		Y=38512851.131m		初见水位深度		测量日期		2025.6.13	
地质时代	层号	层底标高(m)	层底深度(m)	分层厚度(m)	柱状图 1:150	地 层 描 述			取 样 编 号 深度(m)	标贯 实测 击数(击) 深度(m)			
q ₄ ^{ml}	①	5.40	3.50	3.50		素填土:灰褐色、红褐色,松散,主要由粘性土填成,夹碎石、砼块,顶部约0.2米为砼路面。			1	10.0 1.85-2.15			
									1.50-1.70				
q ₄ ^{al}	② ₁	3.00	5.90	2.40		粉质黏土:黄褐色、灰褐色,软塑-软可塑,切面较光滑,粘性及韧性较好,干强度较高。			2	6.0 5.15-5.45			
									4.70-4.90				
q ₄ ^{al}	② ₂	-5.50	14.40	8.50		淤泥质土:灰黑色、深灰色,流塑,具腥臭味,夹砂、局部夹腐木,上部约2.1米夹流塑、软塑粘性土。			3	3.0 9.55-9.85			
									9.10-9.30				
q ₄ ^{al}	② ₃	-8.50	17.40	3.00		中细砂:灰褐色,松散-稍密,饱和,主要成分为石英,级配差,砂质不存,局部夹淤泥。			4	10.0 15.75-16.05			
									15.30-15.50				
广东中盛市政工程设计有限公司													
外业日期: 2025.6.12				制表: 				校核: 					




钻孔柱状图

工程名称		东莞市桥头镇东太湖产业园规划一路道路工程					工程编号		GDZS2525-026	
孔 号		LK3		坐	X=2547393.056m		钻孔直径		稳定水位深度	2.30m
孔口标高		8.10m		标	Y=38512907.708m		初见水位深度		测量日期	2025.6.13
地质时代	层号	层底标高 (m)	层底深度 (m)	分层厚度 (m)	柱状图 1:150	地 层 描 述		取 样 编 号 深度(m)	标贯 实测 击数(击) 深度(m)	
q _{ml} 4	①	4.80	3.30	3.30		素填土:灰褐色、红褐色,松散,主要由粘性土填成,夹碎石、砼块,顶部约0.2米为砼路面。	1	1.40-1.60	9.0	1.75-2.05
							2	4.60-4.80	7.0	5.05-5.35
q _{al} 4	② ₁	1.60	6.50	3.20		粉质黏土:黄褐色、灰褐色,软塑-软可塑,切面较光滑,粘性及韧性较好,干强度较高。	3	8.70-8.90	2.0	9.15-9.45
							4	13.30-13.50	11.0	13.75-14.05
q _{al} 4	② ₂	-4.50	12.60	6.10		淤泥质土:灰黑色、深灰色,流塑,具腥臭味,夹砂、局部夹腐木。				
q _{al} 4	② ₃	-7.90	16.00	3.40		中细砂:灰褐色,松散-稍密,饱和,主要成分为石英,级配差,砂质不存,局部夹淤泥、下部约1.2米夹灰黄色中粗砂。				
广东中盛市政工程设计有限公司										
外业日期: 2025.6.11					制表: 			校核: 		





钻孔柱状图

工程名称		东莞市桥头镇东太湖产业园规划一路道路工程					工程编号		GDZS2525-026	
孔 号		LK4		坐	X=2547482.329m		钻孔直径		稳定水位深度	2.70m
孔口标高		8.50m		标	Y=38512911.678m		初见水位深度		测量日期	2025.6.13
地质时代	层号	层底标高(m)	层底深度(m)	分层厚度(m)	柱状图 1:150	地 层 描 述		取 样 编 号 深度(m)	标贯 实测 击数(击) 深度(m)	
q ₄ ^{ml}	①	5.30	3.20	3.20		素填土:灰褐色、红褐色,松散,主要由粘性土填成,夹碎石、砼块,。		1 2.30-2.50	10.0 2.75-3.05	
	② ₁	0.30	8.20	5.00		粉质黏土:黄褐色、灰褐色,软塑-软可塑,切面较光滑,粘性及韧性较好,干强度较高。		2 5.60-5.80	8.0 6.05-6.35	
	② ₂	-4.10	12.60	4.40		淤泥质土:灰黑色、深灰色,流塑,具腥臭味,夹砂、局部夹腐木。		3 9.10-9.30	4.0 9.55-9.85	
	② ₃	-6.90	15.40	2.80		中细砂:灰褐色,松散-稍密,饱和,主要成分为石英,级配差,砂质不存,局部夹淤泥。		4 13.10-13.30	10.0 13.55-13.85	

钻孔柱状图

工程名称		东莞市桥头镇东太湖产业园规划一路道路工程					工程编号		GDZS2525-026	
孔 号		LK5		坐	X=2547566.632m		钻孔直径		稳定水位深度	2.40m
孔口标高		8.20m		标	Y=38512899.205m		初见水位深度		测量日期	2025.6.13
地质时代	层号	层底标高(m)	层底深度(m)	分层厚度(m)	柱状图 1:150	地 层 描 述		取 样 编 号 深度(m)	标贯 实测 击数(击) 深度(m)	
q _{ml} 4	①	4.80	3.40	3.40		素填土:灰褐色、红褐色,松散,主要由粘性土填成,夹碎石、砼块,顶部约0.2米为砼路面。		1 2.20-2.40	12.0 2.55-2.85	
						粉质黏土:黄褐色、灰褐色,软塑-软可塑,切面较光滑,粘性及韧性较好,干强度较高。				
						淤泥质土:灰黑色、深灰色,流塑,具腥臭味,夹砂、局部夹腐木。				
						中细砂:灰褐色,松散-稍密,饱和,主要成分为石英,级配差,砂质不存,局部夹淤泥。				
q _{al} 4	② ₁	0.90	7.30	3.90				2 6.30-6.50	6.0 6.75-7.05	
q _{al} 4	② ₂	-3.90	12.10	4.80				3 8.70-8.90	4.0 9.15-9.45	
q _{al} 4	② ₃	-7.30	15.50	3.40				4 13.50-13.70	11.0 13.95-14.25	

钻孔柱状图

工程名称						东莞市桥头镇东太湖产业园规划一路道路工程						工程编号		GDZS2525-026								
孔 号		LK6		坐		X=2547634.457m		钻孔直径				稳定水位深度		2.10m								
孔口标高		7.80m		标		Y=38512900.681m		初见水位深度				测量日期		2025.6.13								
地质时代	层号	层底 标高 (m)	层底 深度 (m)	分层 厚度 (m)	柱状图 1:150	地 层 描 述						取 样 编 号 深度(m)	标贯 实测 击数(击) 深度(m)									
q _{ml} 4	①	4.60	3.20	3.20		素填土:灰褐色、红褐色,松散,主要由粘性土填成,夹碎石、砼块,顶部约0.2米为砼路面。						1	8.0 2.55-2.85									
												1.40-1.60										
												2										
												5.10-5.30										
q _{al} 4	② ₁	1.20	6.60	3.40		粉质黏土:黄褐色、灰褐色,软塑-软可塑,切面较光滑,粘性及韧性较好,干强度较高。						3	7.0 5.55-5.85									
												7.40-7.60										
												4										
												12.40-12.60										
q _{al} 4	② ₂	-3.70	11.50	4.90		淤泥质土:灰黑色、深灰色,流塑,具腥臭味,夹砂、局部夹腐木、下部相变为流塑-软塑状粘性土。						4	4.0 7.95-8.25									
												7.40-7.60										
												4										
												12.40-12.60										
q _{al} 4	② ₃	-7.40	15.20	3.70		中细砂:灰褐色、黄褐色,松散-稍密,饱和,主要成分为石英,下部夹黄褐色中粗砂,级配稍好。						4	19.0 12.75-13.05									
												7.40-7.60										
												4										
												12.40-12.60										
广东中盛市政工程设计有限公司															制表:				校核:			
外业日期: 2025.6.10																						